




Hose reel HM 400

EBINGER

Technisches Equipment



- Security Handle-System that allows the handle to stay in the place, avoiding the rotation during the manual hose unreeling
- Sturdy drum
- Casing in painted steel or stainless steel
- Adjustable rewinding break
- Stable mounting bracket
- Drum supporting brushings made from TENAXID
- Max. 40m hose, max. 1/2" hose



Medium	Casing	Length of the hose	Max. pressure	Max. temp.	swivel	Swivel connection	Item-No.
Water - air	painted steel stainless steel	without hose	20bar	90°C	brass	1/2" F	8.400.100 8.404.100
High pressure 100	painted steel stainless steel	without hose	100bar	130°C	stainless steel	1/2" F	8.400.200 8.404.200
High pressure 200	painted steel stainless steel	without hose	200bar	130°C	stainless steel	3/8" F	8.400.300 8.404.300
High pressure 400	painted steel stainless steel	without hose	400bar	130°C	stainless steel	3/8" F	8.400.400 8.404.400
Oil	painted steel	without hose	150bar	60°C	steel zined	1/2" F	8.400.900
Grease	painted steel stainless steel	without hose	600bar	60°C	steel zined	3/8" F	8.400.500 8.404.500
Diesel	painted steel stainless steel	without hose	10bar	-	brass	1/2" F	8.400.100 8.404.100

outer Ø		length	
	1/4"	14mm	Max. 40m
	3/8"	17mm	Max. 18m
	1/2"	20mm	Max. 15m
	5/8"	21mm	Max. 12m
	3/4"	27mm	Max. 8m

