




# Hose reel HM 610

# EBINGER

Technisches Equipment



- Security Handle-System that allows the handle to stay in the place, avoiding the rotation during the manual hose unreeling
- Sturdy drum
- Casing in painted steel or stainless steel
- Adjustable rewinding break
- Stable mounting bracket
- Drum supporting brushings made from TENAXID
- Max. 110m hose, max. 1" hose



Medium	Casing	Length of the hose	Max. pressure	Max. temp.	swivel	Swivel connection	Item-No.
Water - air	painted steel stainless steel	without hose	20bar	90°C	brass	½" F	8.610.100 8.614.100
	painted steel stainless steel	without hose	20bar	90°C	brass	1" F	8.610.130 8.614.130
High pressure 100	painted steel stainless steel	without hose	100bar	130°C	stainless steel	½" F	8.610.200 8.614.200
	painted steel stainless steel	without hose	100bar	130°C	stainless steel	1" F	8.610.230 8.614.230
High pressure 200	painted steel stainless steel	without hose	200bar	130°C	stainless steel	¾" F	8.610.300 8.614.300
High pressure 400	painted steel stainless steel	without hose	400bar	130°C	stainless steel	¾" F	8.610.400 8.614.400
Oil	painted steel	without hose	150bar	60°C	steel zined	½" F	8.610.900
	painted steel	without hose	150bar	60°C	steel zined	1" F	8.610.930
Grease	painted steel stainless steel	without hose	600bar	60°C	steel zined	¾" F	8.614.500 8.614.500
Diesel	painted steel stainless steel	without hose	10bar	-	brass	1" F	8.614.130 8.614.130

outer Ø		length	
	1/4"	14mm	Max. 110m
	3/8"	17mm	Max. 60m
	1/2"	20mm	Max. 45m
	5/8"	21mm	Max. 25m
	3/4"	27mm	Max. 20m
	1"	34mm	Max. 15m

